

Models	MPS-6015W	MPS-6015L	MPS-6090-120	MPS-6090-220
<b>Input</b>				
Voltage	220 VAC	220 VAC	120 VAC	220 VAC
Voltage Range	+ / - 15%			
Frequency	50 Hz	60 Hz	60 Hz	50 Hz
Protection	Fuse (8A)	Fuse (8A)	Fuse (15A)	Fuse (15A)
Power Factor	≥ 0.9(full load)			
<b>Output</b>				
Voltage	60 VAC	60 VAC	60/90VAC, selectable	60/90VAC, selectable
Regulation	+ / - 5%			
Waveform	Quasi-square			
Current	15A			
Power	900 VA	900 VA	900 VA	1350 VA
Protection	Current limited			
Short Current	150 % of max. current rating			
Efficiency	≥ 90%			
<b>Time Delay Relay</b>				
Initialization	10s (selectable, TDR is an optional feature)			
<b>Mechanical</b>				
Input Connection(s)	Terminal Block			
Output Connection(s)	5/8" female			
Enclosure Material	Aluminum			
Finish	Powder coating			
Dimensions	335 x 217 x 190mm			
<b>Environmental</b>				
Operating Temperature	- 40°C to 55°C			
Humidity	0 to 95% non-condensing			



- \* Constant voltage ferroresonant transformer
- \* Fully regulated, clean and reliable output AC power
- \* Input and output protection, lightning surge protection
- \* Current limited output and short-circuit protection
- \* Automatic restart upon removal of short
- \* Field selectable output voltages
- \* Powder coated enclosure for outdoor applications
- \* Pole & wall mount installations
- \* 5/8" female output connection
- \* Durable LED indicator
- \* Optional Time Delay Relay (TDR)

1. More voltage configurations may be available. Please download the datasheet or contact us directly for more details.
2. Due to continuing improvements, the product is subject to change without prior notice.

